

KLEEN-TEX SPECIFICATION

# FITTED ENTRANCE SYSTEMS

High performance, heavy footfall  
entrance matting systems for  
commercial applications



**Kleen-Tex**  
make more of your floor



[www.kleen-tex.co.uk/entrance-systems](http://www.kleen-tex.co.uk/entrance-systems)



# PROFESSIONAL ENTRANCE SOLUTIONS

For over 50 years, Kleen-Tex has manufactured floor mats and matting solutions for commercial applications that deliver the highest standards of quality and performance.

Operating over five continents, we have extensive experience in textiles and design, floor care, pedestrian safety, entrance systems and specialist floor mat solutions.

Our extensive portfolio of high performance entrance systems are expertly designed and manufactured to provide unrivalled durability and safety for high-footfall public entrances.

This includes tile and grid systems that are available in a variety of textures, colours and solid rubber finishes. All of which can be tailored to meet your project’s unique functional and aesthetic requirements to ensure successful specification.

As a leading designer and manufacturer of commercial flooring matting systems, we are committed to supporting the reduction of plastic waste, whilst simultaneously aiding professionals in improving the environmental efficiency of commercial projects.

# CONTENTS

## GRID SYSTEMS

|              |    |
|--------------|----|
| G-Guard      | 4  |
| G-Guard Eco  | 12 |
| Kleen-System | 16 |

## TILE SYSTEMS

|                |    |
|----------------|----|
| Concourse Tile | 26 |
| Matrix Tile    | 27 |

### KEY



Suitable for indoor use



Highly absorbent



Suitable for outdoor use



Suitable for high foot traffic areas



Suitable for wheelchair users



Environmentally friendly



# G-GUARD

ENTRANCE MATTING SYSTEM

# HIGH PERFORMANCE ENTRANCE MATTING SYSTEM FOR HEAVY FOOTFALL AREAS

Manufactured in Britain to the highest environmental standards, our G-Guard range is Green Spec accredited and supplied with a 15 year manufacturers warranty as standard.

The efficient flooring system consistently removes foot-borne dirt and moisture from high traffic areas, whilst simultaneously providing the highest standards of aesthetics.

## For Exterior Entrance applications:

- Removes dirt, grit, grease and initial moisture prior to entering the building.
- Choice of entrance matting ranges
- Drainage options are available
- Anodised aluminium grid system
- Legislation compliant, DDA compliant
- Easy to clean and maintain
- 40 year base + 10 year fabric guarantee
- Made in Europe

Constructed from 90% recycled aluminium, the rigid base is considerably stronger than PVC, rubber and wired alternatives and performs for 30-40 years.

Infills can be cost-effectively replaced and are available in a diverse range of colours to suit specific project requirements and a 40 year base guarantee and 10 year fabric guarantee offers peace of mind.

## For Primary Entrance applications: *(immediately inside)*

- Removes and collects dirt and moisture from foot and wheeled traffic
- Stops dirt tracking onto the internal flooring
- Prevent slips and trips
- Anodised aluminium grid system
- Legislation compliant, DDA compliant
- Easy to clean and maintain
- 40 year base + 10 year fabric guarantee
- Made in Europe

## ANODISED GRIDS

Kleen-Tex offers a variety of aluminium anodising colour options to provide enhanced design freedom to meet the unique requirements of each entrance area.

By anodising the aluminium, it forms an oxide coating that provides increased resistance, whilst simultaneously providing a colour matching service to complement the chosen interior design scheme or branding.

For aluminium, the anodising process forms a layer of aluminium oxide or corundum, which is very hard, relatively inert, electrically insulating and can absorb dyes to colour the film.

This increases the durability of the aluminium and therefore enhances the appearance and longevity of the entrance matting system.

| COLOUR       | BLACK   | LIGHT GOLD  | MEDIUM GOLD   | DARK GOLD   | GUN METAL GREY   | LIGHT BRONZE  | MEDIUM BRONZE   | DARK BRONZE   |
|--------------|---|---|---|---|--|---|---|---|
| SAMPLE       |  |  |  |  |  |  |  |  |
| MODULE WIDTH | Up to 4000mm  | Up to 2600mm  | Up to 2600mm  | Up to 2600mm  | Up to 2500mm   | Up to 1600mm  | Up to 4000mm  | Up to 4000mm  |
| DC001        | X   | X   | X   | X   | X  | X   | X   | X   |
| DC003        | X   | X   | X   | X   | X  | X   | X   | X   |
| DC004        | X   | X   | X   | X   |  | X   | X   | X   |
| DC005        | X   | X   | X   | X   | X  | X   | X   | X   |
| DC008        | X   | X   | X   | X   | X  | X   | X   | X   |
| DC022        | X   | X   | X   | X   | X  | X   | X   | X   |



AVAILABLE COLOURS:



A heavy duty, dense entrance matting system that withstands extreme foot traffic conditions.

KEY FEATURES

- High foot traction
- Hardwearing finish
- Bespoke manufacturing
- Made in Britain

SUGGESTED APPLICATIONS

- Heavy foot and trolley traffic areas
- Sports venues, subject to spikes and studs

| SIZE   | CONFORMITY  | COMPOSITION   | GUARANTEE                              |
|--|---|---|--|
| <p><b>HEIGHT</b><br/>Low Profile - 12mm<br/>Standard Profile - 17mm</p> <p><b>WIDTH</b><br/>Up to 4000mm</p> | <p>ISO9001:2008<br/>BS8300 DDA Regulations<br/>BS4790:1987 (1996)</p> | <p><b>GRID</b><br/>Minimum 95% recycled rubber in closed construction format</p> <p><b>INSERT</b><br/>Heavy duty fibre bonded polypropylene</p> | <p>10 year manufacturers guarantee</p> |



AVAILABLE COLOURS:

|              |           |           |
|--------------|-----------|-----------|
| AZURE BLUE   | BANK GREY | BEIGE     |
| BLUE         | CHARCOAL  | CHOCOLATE |
| DOLPHIN BLUE | GREEN     | LAGOON    |
| PURPLE       | RED       | SCARLETT  |
| SILVER       | WILLOW    |           |

An extremely hard wearing, durable commercial entrance matting system that facilities low maintenance costs due to robust composition and multi-directional pile.

KEY FEATURES

- Hard wearing and durable
- Made with recycled content
- Fray and unravel resistant
- Sound dampening properties
- Low upkeep costs
- Made in Britain


SUGGESTED APPLICATIONS

- Public buildings
- Corporate entrances

| SIZE   | CONFORMITY  | COMPOSITION  | GUARANTEE                              |
|--|---|--|--|
| <p><b>HEIGHT</b><br/>Low Profile - 12mm<br/>Standard Profile - 17mm</p> <p><b>WIDTH</b><br/>Up to 4000mm</p> | <p>ISO9001:2008<br/>BS8300 DDA Regulations<br/>BS4790:1987 (1996)</p> | <p><b>GRID</b><br/>Minimum 95% recycled rubber in closed construction format</p> <p><b>INSERT</b><br/>85% heavy duty polypropylene, 15% recycled polyester</p> | <p>10 year manufacturers guarantee</p> |



AVAILABLE COLOURS:



A resilient entrance matting system that features high absorbency and is easy to maintain due to its natural occurring infill material composition, which delivers a contemporary aesthetic.

**KEY FEATURES**

- High absorbency profile
- Naturally occurring infill material
- Bespoke manufacturing
- Made in Britain

**SUGGESTED APPLICATIONS**

- High footfall areas
- Public buildings
- Libraries
- Retail Outlets
- Education sector

| SIZE   | CONFORMITY  | COMPOSITION   | GUARANTEE                              |
|--|---|---|--|
| <p><b>HEIGHT</b><br/>Low Profile - 12mm<br/>Standard Profile - 17mm</p> <p><b>WIDTH</b><br/>Up to 4000mm</p> | <p>ISO9001:2008<br/>BS8300 DDA Regulations<br/>BS4790:1987 (1996)</p> | <p><b>GRID</b><br/>Minimum 95% recycled rubber in closed construction format</p> <p><b>INSERT</b><br/>100% natural brush coir</p> | <p>10 year manufacturers guarantee</p> |



AVAILABLE COLOURS:



A hygienic and economical entrance matting system that features a non-slip ribbed top surface infill with high grip cloth finished bottom to provide a hard wearing anti-slip entrance covering.

**KEY FEATURES**

- High foot traction
- Hardwearing finish
- Bespoke manufacturing
- Made in Britain


**SUGGESTED APPLICATIONS**

- Heavy foot and trolley traffic areas
- Sports venues, subject to spikes and studs

| SIZE   | CONFORMITY  | COMPOSITION   | GUARANTEE                              |
|--|---|---|--|
| <p><b>HEIGHT</b><br/>Low Profile - 12mm<br/>Standard Profile - 17mm</p> <p><b>WIDTH</b><br/>Up to 4000mm</p> | <p>ISO9001:2008<br/>BS8300 DDA Regulations<br/>BS4790:1987 (1996)<br/>DIN4106 -B2</p> | <p><b>GRID</b><br/>Minimum 95% recycled rubber in closed construction format</p> <p><b>INSERT</b><br/>Natural Rubber and Styrene Butadiene Rubber</p> | <p>10 year manufacturers guarantee</p> |



AVAILABLE COLOURS:



A high performance, durable entrance matting system manufactured from 100% recycled materials. Suitable for a variety of applications that require mitigation against impact, sound, vibration and resistance to mechanical loads.

KEY FEATURES

- Highly durable
- Made from 100% recycled materials
- Long life span
- Sound and vibration resistant
- Made in Britain

SUGGESTED APPLICATIONS

- Sports entrances
- Hospitals
- Schools

| SIZE   | CONFORMITY  | COMPOSITION  | GUARANTEE                              |
|--|---|--|--|
| <p><b>HEIGHT</b><br/>Low Profile - 12mm<br/>Standard Profile - 17mm</p> <p><b>WIDTH</b><br/>Up to 4000mm</p> | <p>ISO9001:2008<br/>BS8300 DDA Regulations<br/>BS4790:1987 (1996)<br/>DIN4106 - B2<br/>DIN51097 - Rated C<br/>BGR181 - Rated R9</p> | <p><b>GRID</b><br/>Minimum 95% recycled rubber in closed construction format</p> <p><b>INSERT</b><br/>100% recycled flecked rubber infills</p> | <p>10 year manufacturers guarantee</p> |



AVAILABLE COLOURS:



A versatile entrance matting system that features a wide rib infill that creates a defined contrast in texture whilst delivering unrivalled scraping action and an enhanced absorbency profile.

KEY FEATURES

- High absorbency profile
- Heavy duty scraping action
- Bespoke manufacturing
- Made in Britain

SUGGESTED APPLICATIONS

- Education sector
- Public buildings
- Libraries
- Retail Outlets

| SIZE   | CONFORMITY   | COMPOSITION   | GUARANTEE                              |
|--|--|---|--|
| <p><b>HEIGHT</b><br/>Low Profile - 12mm<br/>Standard Profile - 17mm</p> <p><b>WIDTH</b><br/>Up to 4000mm</p> | <p>ISO9001:2008<br/>BS8300 DDA Regulations<br/>BS4790:1987 (1996)<br/>EN 95/28 (ECE 118)</p> | <p><b>GRID</b><br/>Minimum 95% recycled rubber in closed construction format</p> <p><b>INSERT</b><br/>Heavy ribbed 100% polypropylene</p> | <p>10 year manufacturers guarantee</p> |



# G-GUARD ECO

# HIGH PERFORMANCE. ECO SENSITIVE.

Our G-Guard Eco range of high performance entrance matting systems are available in an **extensive range of colour options** and can be utilised to create the most sustainable and colourful entrance matting systems for the commercial market.



Contains over 95% of aluminium procured from recycled sources



Features infills that are manufactured with over 80% Cashmere goat hair fibres that are procured from sustainable resources, primarily a by-product of Cashmere goat farming



Features materials that are 100% natural insulators of heat, saving energy and money



Delivers high performance dirt trapping capabilities that reduce dust and air pollution for improved air quality



Supplied with a competitive 15 year manufacturers guarantee for enhanced peace of mind



Manufactured in the UK to minimise carbon footprint in relation to shipping

## YOUR STYLE. YOUR WAY.


EARTH TONES



BERRY BLUES



FOREST SHADE



DEVON SANDS



HIGHLAND FERN



COASTAL BRIGHTS



With over 60 different colours of infill material and 8 different colours of aluminium grid to choose from, G-Guard Eco can be utilised to create a truly unique and exclusive entrance matting system for your entranceway and lobby.



A high performance entrance matting system that features infills manufactured from sustainable materials and available in the most distinctive range of colours to provide unlimited design flexibility.




**KEY FEATURES**

- Bold and vibrant colour range
- Made from recyclable materials
- Extremely hardwearing and durable
- Wheel friendly
- Bespoke manufacturing capabilities
- Made in Britain



**SUGGESTED APPLICATIONS**

- Heavy foot and trolley traffic areas
- Medical practices
- Shopping centres
- Hospitality
- Schools and education



| SIZE   | CONFORMITY  | COMPOSITION   | GUARANTEE   |
|--|---|---|---|
| <b>HEIGHT</b><br>Low Profile - 12mm<br>Standard Profile - 17mm<br><br><b>WIDTH</b><br>Up to 4000mm | ISO9001:2008<br>BS8300 DDA Regulations<br>BS4790:1987 (1996)<br>BS1006:1990 | <b>GRID</b><br>Minimum 95% recycled rubber in closed construction format<br><br><b>INSERT</b><br>Natural goat hair infill | 15 year manufacturers guarantee<br><br>Global Green Tag Certified |



# INFILL COLOUR OPTIONS

|   |   |   |   |   |  |   |   |   |
|---|---|---|---|---|--|---|---|---|
|    |    |    |    |    |    |    |    |    |
| 512<br>Dapple Grey  | 513<br>Sage   | 514<br>Bilberry   | 515<br>Silver   | 516<br>Brilliant Blue   | 517<br>Sky   | 520<br>Damson   | 523<br>Larch  | 524<br>Russet   |
|    |    |    |    |    |    |    |    |    |
| 527<br>Dried Lavender   | 528<br>Apple  | 530<br>Heather  | 532<br>Sisal  | 534<br>Anthracite   | 538<br>Silver Birch  | 542<br>Night Sky  | 555<br>Wild Rice  | 558<br>Peacock  |
|    |    |    |    |    |    |    |    |    |
| 559<br>Burnt Orange   | 562<br>Rose Sunset  | 565<br>Evergreen  | 566<br>Lichen   | 567<br>Lagoon Blue  | 568<br>Jonquille   | 569<br>Clover   | 571<br>Mushroom   | 572<br>Milk Chocolate   |
|    |    |    |    |    |    |    |    |    |
| 573<br>Coffee Bean  | 574<br>Autumn Fern  | 576<br>Aquamarine   | 577<br>Burgundy   | 579<br>Petrol Green   | 580<br>Lettuce Leaf  | 581<br>Deep Purple  | 584<br>Blackberry   | 585<br>Orange Squash  |
|    |    |    |    |    |    |    |    |    |
| 587<br>Double Cream   | 589<br>Amethyst   | 592<br>Lovely Lilac   | 593<br>Diplomat Red   | 601<br>Truffle  | 614<br>Aegean  | 615<br>Fresh Water  | 616<br>Chilli   | 617<br>Magenta  |
|  |  |  |  |  |  |  |  |  |
| 618<br>Indigo   | 619<br>Aubergine  | 620<br>Charcoal   | 622<br>Taupe  | 623<br>Saddle   | 624<br>Dark Chocolate  | 625<br>Denim  | 628<br>Powder   | 631<br>Lipstick   |
|  |  |  |  |  |  |   |   |   |
| 632<br>Black  | 643<br>Melon  | 697<br>Lime   | 698<br>Cornflower   | 699<br>Olive Tang   | 700<br>Antique Rose  |   |   |   |

# GRID OPTIONS

| COLOUR       | BLACK   | LIGHT GOLD  | MEDIUM GOLD   | DARK GOLD   | GUN METAL GREY   | LIGHT BRONZE  | MED. BRONZE   | DARK BRONZE   |
|--------------|---|---|---|---|--|---|---|---|
| SAMPLE       |  |  |  |  |  |  |  |  |
| MODULE WIDTH | Up to 4000mm  | Up to 2600mm  | Up to 2600mm  | Up to 2600mm  | Up to 2500mm   | Up to 1600mm  | Up to 4000mm  | Up to 4000mm  |
| ECO          | X   | X   | X   | X   | X  | X   | X   | X   |



# KLEEN- SYSTEM



# RESILIENT MATTING SYSTEMS FOR FITTED WELLS AND RECESSES

Manufactured in Europe, our aluminium entrance mat system profiles feature a resilient stainless steel wire construction that is suitable for installation throughout entrances that experience normal to heavy pedestrian traffic.

The fitted entrance system is available with three types of inserts that can be tailored to meet specific project requirements, whilst delivering optimum performance.


- Fitted entrance system
- Designed for busy entrance areas
- Extremely hard wearing
- 3 insert types, each in 3 colour options
- Mix and match types and colours
- 3 recess depths available
- Frames and ramps also available
- Cfl-s1 fire certification
- National Institute of Hygiene certification
- 3 year Manufacturers Guarantee
- Made in Europe

**KLEEN-SYSTEM BRUSH** - Designed to absorb moisture, this abrasion and compression resistant fibre fill is suitable for indoor use only.

**KLEEN-SYSTEM RIBBED** - Made with tough, hard rubber this robust fill is resistant to moisture, corrosion and varying temperature extremes. Suitable for indoor or outdoor use.

**KLEEN-SYSTEM SCRUB** - Constructed of strong bristles that actively scrape debris from passing foot traffic. Resistant to moisture, corrosion and varying temperature extremes and also suitable for indoor or outdoor installation.





A highly durable tread surface mounted within an aluminium frame. Designed to absorb moisture, this abrasion and compression resistant fibre fill is for indoor use only.


**KEY FEATURES**

- Effective cleaning function
- High foot traction
- Hardwearing finish
- Abrasion and crush resistant
- Bespoke manufacturing
- Made in Europe

**SUGGESTED APPLICATIONS**

- Shopping centres
- Offices
- Public buildings
- Leisure facilities
- Hospitals

| SIZE   | CONFORMITY   | COMPOSITION   | GUARANTEE                         |
|--|--|---|-----------------------------------|
| <b>HEIGHT</b><br>12mm, 17mm, 22mm,<br><br><b>WIDTH</b><br>No maximum width | PZH HK/B/0628/01/2014<br>ITB NJ-5/KR/1106/09<br>48/09/BB91133001<br>10/11/BB91104001<br>DIN 51130:2014-02:R11<br>Cfl-s11 | <b>PROFILE</b><br>Aluminium with stainless<br>steel wire<br><br><b>INSERT</b><br>Looped polypropylene | 3 year manufacturers<br>guarantee |



Made with tough, hard rubber this robust fill is resistant to moisture, corrosion and varying temperature extremes. Use indoor or outdoor.


**KEY FEATURES**

- Strong mud and moisture removal properties
- Effective cleaning function
- Abrasion and crush resistant
- Resistant to humidity, corrosion and heat
- Bespoke manufacturing
- Made in Europe

**SUGGESTED APPLICATIONS**

- Shopping centres
- Offices
- Public buildings
- Leisure facilities
- Hospitals

| SIZE  | CONFORMITY   | COMPOSITION  | GUARANTEE                             |
|---|--|--|---------------------------------------|
| <p><b>HEIGHT</b><br/>12mm, 17mm, 22mm,</p> <p><b>WIDTH</b><br/>No maximum width</p> | <p>PZH HK/B/0628/01/2014<br/>ITB NJ-5/KR/1106/09<br/>48/09/BB91133001<br/>10/11/BB91104001<br/>DIN 51130:2014-02:R12<br/>Cfl-s11</p> | <p><b>PROFILE</b><br/>Aluminium with stainless steel wire</p> <p><b>INSERT</b><br/>Hard rubber</p> | <p>3 year manufacturers guarantee</p> |



Strong bristles actively scrape debris from passing foot traffic. This fill is also resistant to moisture, corrosion and varying temperature extremes. Use indoor or outdoor.

**KEY FEATURES**

- Extremely hard wearing
- Designed for busy entrances
- Long life span
- Resistant to humidity, corrosion and heat
- Bespoke manufacturing
- Made in Europe

**SUGGESTED APPLICATIONS**

- Shopping centres
- Offices
- Public buildings
- Leisure facilities
- Hospitals

| SIZE  | CONFORMITY   | COMPOSITION  | GUARANTEE                             |
|---|--|--|---------------------------------------|
| <p><b>HEIGHT</b><br/>12mm, 17mm, 22mm,</p> <p><b>WIDTH</b><br/>No maximum width</p> | <p>PZH HK/B/0628/01/2014<br/>ITB NJ-5/KR/1106/09<br/>48/09/BB91133001<br/>10/11/BB91104001<br/>DIN 51130:2014-02:R13<br/>Cfl-s11</p> | <p><b>PROFILE</b><br/>Aluminium with stainless steel wire</p> <p><b>INSERT</b><br/>Rigid scraper tufts</p> | <p>3 year manufacturers guarantee</p> |

Kleen-System Duo

Our individual Kleen-System modules can be combined to create new combinations with unique properties to ensure your entrance solution services your need as effectively as possible.

Kleen-System Duo **Brush/Ribbed**



Combines a strong scraping action with efficient moisture control properties. Suitable for indoor use only.



Kleen-System Duo **Scrub/Brush**



Highly effective against removal of soil and dirt with efficient moisture control properties. Suitable for indoor use only.



Kleen-System Duo **Scrub/Ribbed**



Impressive effectiveness in removal of heavy soil and dirt. Suitable for indoor and outdoor use.



# FRAMES

To ensure a level and stable installation, it is essential that the Kleen-System range is installed on a level base. An uneven surface could lead to vibrations and the mat could be permanently deformed as a result (necessitating replacement).

Kleen-System offers casting frames in multiple sizes and thicknesses to accommodate the variety of infill materials in the Kleen-System range.

It isn't always possible to sit your Kleen-System aluminium mat within a recess or well area and occasionally the product will need to sit on top of a floor surface.

To allow for accessibility and ease of movement, Kleen-System also offer ramp profiles at varying heights to allow for free movement of wheelchairs and trolleys for example.




Warsaw Spire  
Kleen-System Brush Black and Grey





6912-1e  
6912-1e9  
oftech.croat





# TILE SYSTEMS



Concourse is a primary matting system for use in commercial applications where the removal of foot borne contaminants at entrance ways is essential. The matting modules are supplied as solid moulded units in 12 mm and 18 mm thickness.



**KEY FEATURES**

- Slip resistant profile
- Unlimited modular size
- 100% natural rubber
- Simple to fit
- No minimum order quantity
- Made in Britain

**SUGGESTED APPLICATIONS**

- Heavy foot and trolley traffic areas
- Medical practices
- Shopping centres
- Hospitality
- Schools and education

| SIZE   | CONFORMITY   | COMPOSITION                            | GUARANTEE                      |
|--|--|--|--------------------------------|
| <b>MODULE SIZE</b><br>500mm x 1000mm<br><br><b>DEPTH</b><br>12mm or 18mm | BS 6307:1982(2003)/<br>DOC-FF-1-70<br>BS 4790:1987 (2014)<br>TM 144:2011 | Polymer enhanced heavy-duty SBR Rubber | 1 year manufacturers guarantee |





Matrix Tile is a primary matting system for use in commercial applications where the removal of foot borne contaminants at entrance ways is essential. The matting modules are supplied as solid units complete with nylon wiper pads and 2 thicknesses.



**KEY FEATURES**

- Slip resistant profile
- Unlimited modular size
- 100% natural rubber
- Simple to fit
- No minimum order quantity
- Made in Britain

**SUGGESTED APPLICATIONS**

- Heavy foot and trolley traffic areas
- Medical practices
- Shopping centres
- Hospitality
- Schools and education

| SIZE                                 | CONFORMITY   | COMPOSITION   | GUARANTEE                         |
|--------------------------------------|--|---|-----------------------------------|
| <b>MODULE SIZE</b><br>500mm x 1000mm | BS 6307:1982(2003)/<br>DOC-FF-1-70<br>BS 4790:1987 (2014)<br>TM 144:2011 | <b>SURFACE</b><br>Solution dyed nylon                       | 1 year manufacturers<br>guarantee |
| <b>DEPTH</b><br>12mm or 18mm         |  | <b>BACKING</b><br>Polymer enhanced heavy<br>duty SBR rubber |                                   |





# OUR COMMITMENT TO SUSTAINABLE CONSTRUCTION

As a leading global manufacturer of floor matting systems, we understand our responsibility to continuously improve the sustainability of our products and operations.



## PROCURING RECYCLED MATERIALS

Whilst procuring recycled materials for our products is essential, we are also developing end of life options for our products across all Kleen-Text brands.

For example, our solid rubber mats can be re-crumbled for use in new products to reduce the consumption and processing of new raw materials.

We are also continuously exploring how we can extend our dedicated range of floor matting systems that are manufactured from recycled materials, including 100% ECONYL® regenerated nylon made entirely from ocean and landfill waste.

Our **EcoAbsorb** product is manufactured from Renycle™ 50 recycled yarn, which, compared to standard yarn, saves energy, reduces CO2 emissions, reduces water consumption and reduces waste material during production.

We also utilise fabric constructed from recycled PET plastic bottles and 15% recycled nitrile rubber.

Our **EcoAbsorb** floor matting system also dries 37% faster than a cotton mat, saving valuable energy, time and money during laundry cycles.



## REDUCING OUR CARBON FOOTPRINT

We are also undertaking a series of initiatives as part of our commitment to minimising our carbon footprint.

From a logistics perspective, we are proactively consolidating our deliveries with the aim of sending full truckloads to eliminate any empty shipping space.

We have also implemented reduced travel frequency for staff, with increased use of conference call technology and working from home with virtual offices.

Wherever possible, we are reducing waste across our global operations and recycling at every opportunity.



## ADOPTING EFFICIENT PROCESSES

ISO 14001:2015 is implemented throughout all aspects of our operations and we are continuously identifying how we can increase our operational efficiencies across all aspects of our business.

This includes a reduction in packaging and palette use, the introduction of recyclable packaging and increasing our use of renewable energy throughout our supply chain.



## BE PART OF THE ENTRANCE REVOLUTION

See how our highly effective, heavy footfall entrance matting systems can reduce your cleaning costs whilst improving the aesthetics of your entrance.

[www.kleen-tex.co.uk/entrance-systems](http://www.kleen-tex.co.uk/entrance-systems)

---

### **Elliot Brankley**

Sales Manager

**Phone** +44 (0) 1204 705070

**Mob** +44 (0) 7880 032643

**Email** [ebrankley@kleen-tex.com](mailto:ebrankley@kleen-tex.com)

 **Kleen-Tex**  
make more of your floor