





Step up to long lasting, cost effective protection

A hygienic and economical entrance matting system that features a non-slip ribbed top surface infill with high grip cloth finished bottom to provide a hard wearing anti-slip entrance covering.

Why Choose DC005?

- » First point of contact entrance solution
- » Perfect for high traffic areas
- » Hardwearing finish
- » Hygienic and economical solution
- » Sound dampening properties
- » Easy to clean dirt collection channel
- » Bespoke manufacturing to specification
- » 10 years Manufacturers Guarantee
- » Made in Britain

Technical Details

Materials

- » Natural rubber and styrene butadiene rubber
- » Minimum 95% recycled aluminium grid

Applications

- » Heavy foot traffic areas
- » Sports venues subject to spikes and studs

Certifications

- » ISO9001:2008
- » BS4790:1987 (1996)
- » BS8300 DDA Regulations
- » DIN4106-B2

Sizing

Infill Height

- » Low Profile - 12 mm
- » Standard Profile - 17 mm

Panel Widths

- » Up to 4000 mm

Length

- » Modular - no maximum length



Black

Colours are subject to commercial tolerance.

Full Technical Data



For more information, please contact our Customer Service Team:

T: +44 (0)1204 70 50 70

E: info@kleen-tex.co.uk

 **Kleen-Tex**
make more of your floor