



Grid System

Kleen-Fit Guard DC008

Recycled Rubber Infill





Unleash the power of tough floor protection

A high performance, durable entrance matting system manufactured from 100% recycled materials. Suitable for a variety of applications that require mitigation against impact, sound, vibration and resistance to mechanical loads.

Why Choose DC008?	Technical Details	Sizing
<ul style="list-style-type: none"> » Our most eco-friendly entrance system » Made with 100% recycled infill material » Highly durable surface » Long life span » Sound and vibration resistant » Easy to clean dirt collection channel » Bespoke manufacturing to specification » 10 years Manufacturers Guarantee » Made in Britain 	<p>Materials</p> <ul style="list-style-type: none"> » 100% recycled flecked rubber infill » Minimum 95% recycled aluminium grid <p>Applications</p> <ul style="list-style-type: none"> » Extremely high foot traffic areas » Sports entrances » Hospitals » Education Sector <p>Certifications</p> <ul style="list-style-type: none"> » ISO9001:2008 » DIN4106 - B2 » BS4790:1987 (1996) » DIN51097 - Rated C » BS8300 DDA Regulation 	<p>Infill Height</p> <ul style="list-style-type: none"> » Low Profile - 12 mm » Standard Profile - 17 mm <p>Panel Widths</p> <ul style="list-style-type: none"> » Up to 4000 mm <p>Length</p> <ul style="list-style-type: none"> » Modular - no maximum length



Black

Blue

Grey

Colours are subject to commercial tolerance.

For more information, please contact our Customer Service Team:

T: +44 (0)1204 70 50 70

E: info@kleen-tex.co.uk

