

Kleen-Fit Guard DC008

Technical Datasheet



Product:	Kleen-Fit Guard DC008	Grid Material:	Aluminium – Minimum 95% recycled content in clo
Category:	Fitted Entrance System	Grid Recycled Content:	95% recycled content
Sub-Category:	Grid System	Anodised Grid Lengths	
Typical Applications:	Extremely high trafic areas such as train stations and airports	Black:	Max. 4000mm
Max Module Length:	4000mm Panels are manufactured specifically to customer requirements. Panel lengths available up to 4000mm left to right as required (Anodised panel lengths vary – see below)	Light Gold:	Max. 2600mm
Installation Method	Recessed in matwell or surface-laid with ramp frame	Medium Gold:	Max. 2600mm
Insert Material:	Flecked rubber infills	Dark Gold:	Max. 2600mm
Insert Depth:	12mm 17mm	Gun Metal Grey:	Max. 2500mm
Origin	Made In Europe	Light Bronze:	Max. 1600mm
		Medium Bronze:	Max. 4000mm
		Dark Bronze:	Max. 4000mm
		Fire Rating:	Hot Metal Nut BS4790:1987 (1996) - Low DIN 4106 – B2
		ISO9001:2018:	Yes
		BS8300 DDA Compliant:	Yes
		BS4790:1987:	Yes
		R9 in accordance with BGR 181:	Yes
		Slip Resistancy:	Slip resistance classification R9 in accordance with BGR 181, Classification C in wet areas in accordance with DIN51097 (the classification for wet areas runs from A to C with C being the best, which guarantees a high level of anti-slip properties) Dynamic coefficient of friction > 0.3µ in accordance with EN 13893



For all mats, we reserve the right of a production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.

10/10/2023