

Kleen-Fit Guard Eco

Technical Datasheet



Product:	Kleen-Fit Guard Eco	Grid Material:	Aluminium – Minimum 100% recycled content in cl
Category:	Fitted Entrance System	Grid Recycled Content:	100% recycled content
Sub-Category:	Grid System	Anodised Grid Lengths	
Typical Applications:	High traffic areas such as residential and care homes, medical practice, offices and administrative buildings, family homes, hotels, retail, sectors, shopping centres, schools, hospitals and airports	Black:	Max. 4000mm
Max Module Length:	4000mm Panels are manufactured specifically to customer requirements. Panel lengths available up to 4000mm left to right as required (Anodised panel lengths vary – see below)	Light Gold:	Max. 2600mm
Installation Method	Recessed in matwell or surface-laid with ramp frame	Medium Gold:	Max. 2600mm
Insert Material:	Natural goat hair infills	Dark Gold:	Max. 2600mm
Insert Depth:	12mm	Gun Metal Grey:	Max. 2500mm
Origin	Made In Europe	Light Bronze:	Max. 1600mm
		Medium Bronze:	Max. 4000mm
		Dark Bronze:	Max. 4000mm
		Light Fastness:	BS 1006: 1990 5-6 very slight to none
		Rubbing Fastness:	BS 1006: 1990 4 very slight
		Water Fastness:	BS 1006: 1990 4 very slight
		ISO9001:2018:	Yes
		BS8300 DDA Compliant:	Yes
		BS4790:1987:	Yes
		Fire Rating:	BS4790: 1987 Mean Radius of burning: 25mm Class: Low
		Fire Rating (additional):	BS EN ISO 11925:2002, BS EN ISO 9239-1: Euroclass Cf-s1 Critical Radiant flux tests: ANSI/ASTM E648 result category 1 AS ISO 9239.1-2003: Direct Stick – CHF value: mean 7.2 kW/m2. Dual bond – CHF value: mean 5.7 kW/m2. Conclusion: Suitable for all commercial/contract installations including institutional, commercial & Public Buildings.



For all mats, we reserve the right of a production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.

10/10/2023